



Used for machining all types of workpiece of irregular shapes.

Standard accessories:

- 1 set of outside hard solid jaws
- 1 set of inside hard solid jaws
- 1 wrench
- 1 set of mounting screws.

Optional accessories:

- 1 set of hard master jaws
- 1 set of soft solid jaws
- 1 set of soft 2-piece jaws (hard master+top soft jaw)

Size 500,630 with T-slots.

二爪自定心卡盘 适用于各种异形工件的加工。

标准配件:

- 一套正爪
- 一套反爪
- 一个扳手
- 一套螺丝

可选配件:

- 一套滑座
- 一套软上爪
- 一套分离爪 (滑座+软上爪)

## K10 SERIES TWO-JAW SELF-CENTERING CHUCKS K10 二爪自定心卡盘

# NTH




卡盘尺寸 Chuck Size	型号 Code No
80	K10-80
100	K10-100
125	K10-125
160	K10-160
200	K10-200
250	K10-250
315	K10-315
400	K10-400



卡盘尺寸 Chuck Size	型号 Code No
80	K10-80S
100	K10-100S
125	K10-125S
160	K10-160S
200	K10-200S
250	K10-250S
315	K10-315S
400	K10-400S

### 尺寸图 Dimensions



### 规格表 SPECIFICATIONS

单位/UNIT:mm

卡盘尺寸 Chuck Size	D <sub>1</sub>	D <sub>2</sub>	D <sub>3</sub>	H <sub>1</sub>	h	Z	D	H
80	55	66	16	50	4	3	M6	66.5
100	72	84	22	55	3	3	M8	74.5
125	95	108	30	58	4	3	M8	84.5
160	130	142	45	65	5	3	M8	94
200	165	180	65	75	6	3	M10	109
250	206	226	80	80	6	3	M12	120
315	260	285	100	90	6	3	M16	147.5
400	340	368	130	112.5	6	3	M16	173.5

### 规格表 SPECIFICATIONS

单位/UNIT:mm

规格/型号D SPEC./MODEL	夹持范围 Max. Gripping Dia		极限转速 Max. speed (r.p.m)	最大静夹持 Max. speed (r.p.m)	毛重 Gross Weight (Kg)
	正爪 Internal Jaws				
K10-80	2-70		4000	8	1.7
K10-100	2-90		3500	10	2.8
K10-125	2.5-125		3000	15	4.7
K10-160	3-160		2500	22	8
K10-200	4-200		2000	28	15
K10-250	6-250		1600	32	25
K10-315	10-315		1200	36	45
K10-400	15-400		1000	40	69

